

## Axle suspension for rigid axles in vehicles

**Publication number:** EP1057665

**Publication date:** 2000-12-06

**Inventor:** BUHL REINHARD (DE)

**Applicant:** ZF LEMFOERDER METALLWAREN AG (DE)

**Classification:**


- international: **B60G7/00; B60G9/00; B60G21/05; B60G7/00; B60G9/00; B60G21/00;** (IPC1-7): B60G9/00; B60G7/00

- european: B60G7/00A; B60G9/00; B60G21/05C



**Application number:** EP20000117760 19960529

**Priority number(s):** DE19951021874 19950616; EP19960919592 19960529

**Also published as:**

 EP1057665 (B1)


**Cited documents:**

 US4084838  
 EP0430368  
 FR2563473  
 DE2505124  
 US4556234  
more >>

[Report a data error here](#)

### Abstract of EP1057665

The axle mounting is for a rigid axle of a commercial vehicle. The multiple linkage and the stabilisation device are configured as a four-point linkage (4) subject to torsional loading and integrating both functions. The four-point linkage is connected to the vehicle body on one side and to the vehicle axle (1) on the other side, via two transverse linkages (5-8) a distance apart from each other. The four-point linkage is connected to the vehicle axle from above.



Data supplied from the [esp@cenet](mailto:esp@cenet) database - Worldwide